

IN THE CLAIMS:

Please amend the claims as follows:

1. (Currently Amended) A method for processing conditional jump instructions in a processor with pipeline computer architecture, the method comprising:
 - (a) loading and decoding a processor instruction, the processor instruction containing an instruction opcode, register addresses, a relative jump distance, a precondition, which specifies under which conditions the instruction is actually to be executed, and a post-condition, which specifies that a conditional jump is to be processed and the corresponding flag bits of an arithmetic-logic unit are to be checked, wherein the post-condition comprises a plurality of post-condition bits that are checked in the processor;
 - (b) checking the precondition, and execution of the decoded processor instruction if the precondition is fulfilled; ~~[[and]]~~
 - (c) in the case of a fulfilled precondition, checking the post-condition, and carrying out no-jump of the post-condition if not fulfilled, and checking the corresponding flag bits, if the post-condition is fulfilled; and
 - (d) jumping to a jump address as a function of the relative jump distance contained in the processor instruction if the post-condition is fulfilled and the checked flag bits are set.
2. (Canceled)
3. (Currently Amended) An apparatus for processing conditional jump instructions in a processor with pipeline computer architecture, the apparatus comprising:
 - (a) an instruction decoder ~~for decoding~~ operable to decode a processor instruction that contains an instruction opcode, register addresses, a relative jump distance, a precondition, ~~which specifies under which~~ configured to specify conditions the instruction is actually ~~to be~~ executed,

and a post-condition, ~~which specifies that~~ configured to specify a conditional jump is ~~to be~~ processed and the corresponding flag bits of an arithmetic-logic unit are to be checked, wherein the post-condition comprises a plurality of post-condition bits that are checked in the processor; and

- (b) wherein the instruction decoder is operable to check, in the case of a fulfilled precondition, whether the post-condition is fulfilled, and, if the post-condition is fulfilled, checking corresponding flag bits, ~~and the checked flag bits are set,~~ if positive, driving a program counter for forming a jump address as a function of the relative jump distance contained in the processor instruction.